

► 22" CLINICAL LCD DISPLAY

# MX-22



► FEATURES

- Compliant with DICOM Part 14 with calibrated greyscale tone and brightness for consistent shading
- Equipotential terminal for safety standard
- Metal casing and NeoV™ Optical glass for easy hygiene and high protection
- Versatile inputs: VGA, DVI, HDMI, DisplayPort, Audio in
- AIP technology: PIP/PBP; 3D Comb Filter / Deinterlace/Noise Reduction
- EcoSmart Sensor allows brightness adjustment by ambient light
- Mounting to fit different clinical environments
- Rigorous screening of the components for mission-critical 24/7 applications
- Selectable aspect ratio for ultimate image
- EN60601-1 and IEC60601-1 medical certification

► SPECIFICATION

<b>Panel</b>	Panel Type	LED-Backlit TFT LCD
	Panel Size	21.5"
	Max. Resolution	FHD 1920 x 1080
	Pixel Pitch	0.2482 mm
	Brightness	250 cd/m <sup>2</sup>
	Contrast Ratio	1,000 :1 (Typical)
	Viewing Angle (H/V)	170°/160°
	Display Colour	16.7M
	Response Time	5 ms
<b>Frequency (H/V)</b>	H. Freq	24 kHz – 82 kHz
	V. Freq	50 Hz – 75 Hz
<b>Input</b>	VGA	15-Pin D-Sub
	DVI	24-Pin DVI-D
	HDMI	HDMI x 1
	DisplayPort	DisplayPort1.2
<b>Audio</b>	Audio in	1 x stereo audio in for PC (audio jack, 3.5 Ø)
	Speaker	2W*2
<b>Power</b>	Power Supply	External
	Power Requirements	DC 12V
	Consumption	<18W (On) <0.3W (Stand-by / Off)
<b>NeoV™</b>	Thickness	3.0 mm (0.12")
<b>Optical Glass</b>	Reflection Rate	< 1.8%
	Transmission Rate	≧ 97%
	Coating Hardness	9H
<b>Operating</b>	Temperature	0°C ~ 40°C (32°F~104°F)
<b>Conditions</b>	Humidity	10%~90% (No condensation)
<b>Storage</b>	Temperature	-20°C ~ 60°C (-4°F~140°F)
<b>Conditions</b>	Humidity	5%~95% (No condensation)
<b>Mounting</b>	VESA FPMPMI	Yes (100 x 100mm & 75 x 75mm)
<b>Security</b>	Kensington Security Socket	Yes
<b>Dimensions</b>	Product w/base (W x H x D)	513 x 369 x 155 mm (20.2" x 14.5" x 6.1")
	Packaging (W x H x D)	602 x 476 x 212 mm (23.7" x 18.7" x 8.34")
<b>Weight</b>	Product Weight (w base)	6.9 kg (15.2 lbs)
	Packaged Weight	9.5 kg (20.9 lbs)
<b>Regulation</b>	Certifications	CE, EN60601-1, IEC60601-1,
<b>Approval</b>	& Compliance	RoHs, WEEE, REACH
<b>Accessories</b>	Supplied	Power Cord, Power Adaptor, 15-Pin D-Sub Cable, Audio Cable

All specifications are subject to change without prior notice

[www.agneovo.com](http://www.agneovo.com)

Copyright © 2017 AG Neovo. All rights reserved.  
The name AG Neovo is a trademark of Associated Industries China, Inc.  
All other trademarks are the property of their respective owners.